



OLDSMOBILE ROCKETS AHEAD




THE POWER SENSATION




OLDSMOBILE

"ROCKET"

Buy with an eye on the engine! And here is the unquestioned leader in engine design today—the sensational Oldsmobile "Rocket"! This is the Futuramic power plant that in one short year has revolutionized modern motoring! The "Rocket's" high-compression action means smoother, quieter, more economical performance than ever before! And the "Rocket" has compiled a first-year record of performance and reliability unmatched in the industry. This is truly the engine of the future, and it's here today—more brilliant than ever!—in the new Futuramic Oldsmobiles!



unbroken, one-piece are of safety plate glass-the rear window curves all the way around to blend into the sides of the body. And for smooth-surging response and handling ease, this is the ear that tops them all with Oldsmobile's Futuramie



"88" CONVERTIBLE COUPÉ

"88" STATION WAGON



"88" 2-DOOR SEDAN

"88" HOLIDAY COUPÉ



NEW Wirlaway HYDRA-MATIC DRIVE

MAKES "ROCKET" PERFORMANCE SMOOTHER THAN EVER



No clutch to push! It's the easiest car in the world to drive. Your left foot rests as you smoothly roll along.

"Smooth—smoother than silk," you'll say when you experience the way new Whirlaway Hydra-Matic Drive pairs with the high-compression "Rocket" Engine. It's Oldsmobile's new "power package"—available in both the glamorous "98" and the famous "88" Oldsmobile! When you step down on the gas, you glide away on a magic carpet of smooth-going power. Saves on gas, too, as new Whirlaway Hydra-Matic is perfectly coordinated with the "Rocket" Engine for maximum efficiency from every ounce of fuel. It's another Oldsmobile first!







4-WAY STABILIZATION

gravity mean more stability, more rugged roadability than ever! Every feature of the chassis assembly is

tested and proven by the craftsmen of Oldsmobile.

Every feature is designed with one thing in mind-

to give you a safer, better ride on every kind of road.

SELF-ENERGIZING SUPER-HYDRAULIC BRAKES



Greater Vision and Luxury with Beautiful New Fisher Bodies




Luxurious new upholstery, including dazzling new nylon fabrics, high-

amics. Seats are broader, roomier, more comfortable—windows are wider, offering a new range of visibility. The inside trim is marked by a new and ultra-modern instrument cluster and a new steering wheel; in fact, every refinement for your motoring pleasure has been included.




POWER-PACKED ECONOMICAL BIG SIX ENGINE


The Big Six Engine, powering the Futuramic Series "76" Oldsmobiles, more than matches many an eight in life and surging acceleration! 105 horsepower means plenty of "go!" And this rugged power plant has set an outstanding record for smooth, economical, trouble-free motoring.




rials. Panoramic visibility in every direction! The windshield sweeps across in an power package—the "Rocket" Engine and new Whirlaway Hydra-Matic Drive! Dazzling new interiors—tailored and trimmed in new Futuramic fabrics and mate-"98"! A beautiful new Body by Fisher-the lowest and widest in Oldsmobile history. around to blend into the sides of the body. And for smooth-surging response and

Here it is! Clamor leader of the Futuramic fleet-the luxurious new Oldsmobile unbroken, one-piece are of safety plate glass-the rear window curves all the way







S P E C I F I C A T I O N S

Six-Cylinder Engine—The "BIG SIX"—Bore, 31½ inches; stroke, 4¾ inches; displacement, 257 cubic inches. Taxable horsepower, 29.9. Brake horsepower, 105 at 3400 r.p.m. Electro-Hardened Aluminum Alloy Pistons fitted with two compression and two oil control rings. Full-pressure lubrication to all main, connecting red prices on and proceedings. connecting rod, piston pin and camshaft bearings, timing chain, and cylinder walls.

FUEL AND COOLING SYSTEM—Down-draft carburetion with built-in automatic choke. Thermostatically controlled cooling and recirculation system. Ballbearing, permanently lubricated water pump. CLUTCH AND TRANSMISSION-Single plate, dry disc clutch. All-Silent Syncro-

HYDRA-MATIC DRIVE—Optional at extra cost.

ELECTRICAL SYSTEM—Under-hood battery, 15-plate, 100-ampere-hour capacity. Air-cooled generator with automatic charging control. Solenoid starter. Unit-type Sealed-Beam headlights with foot selector switch.

FRAME-Rigid-girder, channel X-Member construction. Suspension—Quadri-Coil Springing, with Knee-Action front suspension and heavy coil springs at rear. 4-Way Stabilization through dual stabilizing arms, front and rear ride stabilizers and lateral stabilizer at rear. Double-action

hydraulic shock absorbers, front and rear. STEERING-Dual Center-Control. Worm and double-roller design BRAKES—Super-Hydraulic, self-energizing type. Cast iron braking surfaces. Mechanical parking brake on rear wheels. All brakes completely sealed. Brake lining area, 159.8 square inches. Front lining, 11" x 2"; rear, 11" x 134". TIRES-Low-pressure tires, 7.10 x 15. (Convertible and Station Wagon,

WHEELBASE-1191/2 inches. TURNING CIRCLE DIAMETER-40 feet. Unisteel Turret-Top Bodies by Fisher, completely bonderized and finished

with several coats of high grade lacquer. BODY TYPES—Club Coupe, Convertible Coupe, Holiday Coupe, Club Sedan, 2-Door Sedan, 4-Door Sedan, Station Wagon. (Closed models, standard and de luxe equipment available, as ordered.)

EIGHT-CYLINDER ENGINE—The "ROCKET"—Bore, 3¾ inches; stroke, 3¼ inches; displacement, 303 cubic inches. Taxable horsepower, 45. Brake horsepower, 135 at 3600 r.p.m. Pistons are of the Auto-Thermic type reinforced with two steel struts—with two compression and one oil control rings. Full-pressure lubrication to all main, connecting rod, and camshaft bearings, distributor drive gear, timing chain, and cylinder walls.

FUEL AND COOLING SYSTEM-Down-draft carburetion with built-in automatic choke. Thermostatically controlled cooling and recirculation system. Ball-bearing, leakproof, permanently lubricated water pump. CLUTCH AND TRANSMISSION—10½-inch single plate semi-centrifugal dry disc clutch, Syncro-Mesh Transmission. HYDRA-MATIC DRIVE-Optional at extra cost.

ELECTRICAL SYSTEM—Under-hood battery, 17-plate, 115-ampere-hour capacity. Air-cooled generator with automatic charging control. Solenoid starter. Sealed-Beam headlights.

FRAME-Rigid-girder, channel X-Member type construction. Suspension—Knee-Action front suspension and heavy coil springs at rear. 4-Way Stabilization through dual stabilizing arms, front and rear ride stabilizers and lateral stabilizer at rear. Double-action hydraulic shock absorbers, front and rear.

STEERING-Dual Center-Control. Worm and double-roller. TIRES-7.60 x 15. Low-pressure tires.

BRAKES—Super-Hydraulic, self-energizing type. Cast iron braking surfaces. Mechanical parking brake on rear wheels. All brakes completely sealed. Brake lining area, 191.7 square inches. Front lining, 11" x 2½"; rear lining, 11" x 2". WHEELBASE-1191/2 inches. TURNING CIRCLE DIAMETER-40 feet. UNISTEEL TURRET-TOP BODIES BY FISHER, completely bonderized and finished

with several coats of high grade lacquer. Body Types—Club Coupe, Convertible Coupe, Holiday Coupe, Club Sedan, 2-Door Sedan, 4-Door Sedan, Station Wagon. (Closed models, standard and de luxe equipment available, as ordered.)

EIGHT-CYLINDER ENGINE-The "ROCKET"-Bore, 33/4 EIGHT-CYLINDER ENGINE—The "ROCKET"—Bore, 3¾ inches; stroke, 3¾ inches; displacement, 303 cubic inches. Taxable horsepower, 45. Brake horsepower, 135 at 3600 r.p.m. Pistons are of the Auto-Thermic type reinforced with two steel struts—with two compression and one oil control rings. Full-pressure lubrication to all main, connecting rod, and camshaft bearings, distributor drive gear, timing chain, and cylinder walls.

FUEL AND COOLING SYSTEM-Dual down-draft carburetion with automatic choke. Thermostatically controlled cooling and recirculation system. Ball-bearing, leakproof, permanently lubricated water pump.

CLUTCH AND TRANSMISSION-101/2-inch single plate semi-centrifugal dry disc clutch, Syncro-Mesh Transmission. HYDRA-MATIC DRIVE-Optional at extra cost.

ELECTRICAL SYSTEM—Under-hood battery, 17-plate, 115-ampere-hour capacity. Air-cooled generator with automatic charging control. Solenoid-type starter. Unit-type Sealed-Beam headlights with foot selector switch. FRAME-Rigid-girder, channel X-Member construction.

Suspension—Quadri-Coil Springing, with Knee-Action front suspension and heavy coil springs at rear. 4-Way Stabilization through dual stabilizing arms, front and rear stabilizers and lateral stabilizers at rear. Double-action hydraulic shock absorbers, front and rear. STEERING-Dual Center-Control. Recirculating ball and nut.

TIRES-Low-pressure tires, 7.60 x 15 inches. (Convertible, 8.20 x 15.) Brakes—Super-Hydraulic, self-energizing type. Cast iron braking surfaces. Mechanical parking brake on rear wheels. All brakes completely sealed. Brake lining area, 191.7 square inches. Front lining, 11" x 2½"; rear, 11" x 2".


WHEELBASE-122 inches. TURNING CIRCLE DIAMETER-42 feet.

UNISTEEL TURRET-TOP BODIES BY FISHER, completely bonderized and finished with several coats of high grade lacquer. Body Types—Convertible Coupe, Holiday Coupe, Club Sedan, 4-Door Town Sedan, 4-Door Sedan. (Closed models, standard and de luxe equipment available, as ordered.)

OLDSMOBILE RESERVES THE RIGHT TO MAKE CHANGES AT ANY TIME, WITHOUT NOTICE, IN PRICES, COLORS, MATERIALS, EQUIPMENT, SPECIFICATIONS AND MODELS, AND ALSO TO DISCONTINUE MODELS. WHITE SIDEWALL TIRES, AND OTHER ACCESSORIES AS ILLUSTRATED, OPTIONAL AT EXTRA COST. COPYRIGHT 1890, OLDSMOBILE DIVISION, GENERAL MOTORS CORP., LANSING, MICH., LITHO IN U.S.A.

an outstanding record for smooth, economical, trouble-free motoring. horsepower means plenty of "go!" And this rugged power plant has set more than matches many an eight in life and surging acceleration! 105 The Big Six Engine, powering the Futuramic Series "76" Oldsmobiles,







is marked by a new and ultra-modern a new range of visibility. The inside trim comfortable-windows are wider, offering amics. Seats are broader, roomier, more lights the interiors of the new Futurnew nylon fabrics, highstery, including dazzling Luxurious new uphol-


Fisher Bodies wall lufijus ad Ajiw and Luxury noisiV 1916912












mum efficiency from every ounce of fuel. It's another Oldsmobile first! Matic is perfectly coordinated with the "Rocket" Engine for maxismooth-going power. Saves on gas, too, as new Whirlaway Hydra-

When you step down on the gas, you glide away on a magic carpet of available in both the glamorous "89" and the famous "88" Oldsmobile! sion "Rocket" Engine. It's Oldsmobile's new "power package"way new Whirlaway Hydra-Matic Drive pairs with the high-compres-"Smooth-smoother than silk," you'll say when you experience the



MAKES "ROCKET" PERFORMANCE SMOOTHER THAN EVER





S P E C I F I C A T I O N S

"76"

SIX-CYLINDER ENGINE—The "BIG SIX"—Bore, 31% inches; stroke, 43% inches; displacement, 257 cubic inches. Taxable horsepower, 29.9. Brake horsepower, 105 at 3400 r.p.m. Electro-Hardened Aluminum Alloy Pistons fitted with two compression and two oil control rings. Full-pressure lubrication to all main, connecting rod, piston pin and camshaft bearings,

timing chain, and cylinder walls

FUEL AND COOLING SYSTEM—Down-draft carburetion with built-in automatic choke. Thermostatically controlled cooling and recirculation system. Ballbearing, permanently lubricated water pump.

CLUTCH AND TRANSMISSION—Single plate, dry disc clutch. All-Silent Syncro-Mesh Transmission.

HYDRA-MATIC DRIVE-Optional at extra cost.

ELECTRICAL SYSTEM—Under-hood battery, 15-plate, 100-ampere-hour capacity. Air-cooled generator with automatic charging control. Solenoid starter. Unit-type Sealed-Beam headlights with foot selector switch.

FRAME-Rigid-girder, channel X-Member construction.

Suspension—Quadri-Coil Springing, with Knee-Action front suspension and heavy coil springs at rear. 4-Way Stabilization through dual stabilizing arms, front and rear ride stabilizers and lateral stabilizer at rear. Double-action hydraulic shock absorbers, front and rear.

STEERING-Dual Center-Control. Worm and double-roller design.

BRAKES—Super-Hydraulic, self-energizing type. Cast iron braking surfaces. Mechanical parking brake on rear wheels. All brakes completely sealed. Brake lining area, 159.8 square inches. Front lining, 11" x 2"; rear, 11" x 13".

Tires—Low-pressure tires, 7.10 x 15. (Convertible and Station Wagon, 7.60 x 15.)

WHEELBASE-1191/2 inches. TURNING CIRCLE DIAMETER-40 feet.

UNISTEEL TURRET-TOP BODIES BY FISHER, completely bonderized and finished with several coats of high grade lacquer.

BODY TYPES—Club Coupe, Convertible Coupe, Holiday Coupe, Club Sedan, 2-Door Sedan, 4-Door Sedan, Station Wagon. (Closed models, standard and de luxe equipment available, as ordered.)

"00'

EIGHT-CYLINDER ENGINE—The "ROCKET"—Bore, 3¾ inches; stroke, 3½ inches; displacement, 303 cubic inches. Taxable horsepower, 45. Brake horsepower, 135 at 3600 r.p.m. Pistons are of the Auto-Thermic type reinforced with two steel struts—with two compression and one oil control rings. Full-pressure lubrication to all main, connecting rod, and camshaft bearings, distributor drive

gear, timing chain, and cylinder walls.

FUEL AND COOLING SYSTEM—Down-draft carburetion with built-in automatic choke. Thermostatically controlled cooling and recirculation system. Ballbearing, leakproof, permanently lubricated water pump.

CLUTCH AND TRANSMISSION-10½-inch single plate semi-centrifugal dry disc clutch, Syncro-Mesh Transmission.

HYDRA-MATIC DRIVE-Optional at extra cost.

ELECTRICAL SYSTEM—Under-hood battery, 17-plate, 115-ampere-hour capacity. Air-cooled generator with automatic charging control. Solenoid starter. Sealed-Beam headlights.

FRAME-Rigid-girder, channel X-Member type construction.

Suspension—Knee-Action front suspension and heavy coil springs at rear. 4-Way Stabilization through dual stabilizing arms, front and rear ride stabilizers and lateral stabilizer at rear. Double-action hydraulic shock absorbers, front and rear.

STEERING-Dual Center-Control. Worm and double-roller.

TIRES-7.60 x 15. Low-pressure tires.

BRAKES—Super-Hydraulic, self-energizing type. Cast iron braking surfaces. Mechanical parking brake on rear wheels. All brakes completely sealed. Brake lining area, 191.7 square inches. Front lining, 11" x 2½"; rear lining, 11" x 2". Wheelbase—119½ inches. Turning Circle Diameter—40 feet.

UNISTEEL TURRET. TOP BODIES BY FISHER, completely bonderized and finished with several coats of high grade lacquer.

Body Types—Club Coupe, Convertible Coupe, Holiday Coupe, Club Sedan, 2-Door Sedan, 4-Door Sedan, Station Wagon. (Closed models, standard and de luxe equipment available, as ordered.)

"98'

Eight-Cylinder Engine—The "ROCKET"—Bore, 3¾ inches; stroke, 3½ inches; displacement, 303 cubic inches. Taxable horsepower, 45. Brake horsepower, 135 at 3600 r.p.m. Pistons are of the Auto-Thermic type reinforced with two steel struts—with two compression and one oil control rings. Full-pressure lubrication to all main, connecting rod, and camshaft bearings, distributor drive

gear, timing chain, and cylinder walls.

FUEL AND COOLING SYSTEM—Dual down-draft carburetion with automatic choke. Thermostatically controlled cooling and recirculation system. Ballbearing, leakproof, permanently lubricated water pump.

CLUTCH AND TRANSMISSION—10½-inch single plate semi-centrifugal dry disc clutch, Syncro-Mesh Transmission.

HYDRA-MATIC DRIVE-Optional at extra cost.

ELECTRICAL SYSTEM—Under-hood battery, 17-plate, 115-ampere-hour capacity. Air-cooled generator with automatic charging control. Solenoid-type starter. Unit-type Sealed-Beam headlights with foot selector switch.

FRAME-Rigid-girder, channel X-Member construction.

Suspension—Quadri-Coil Springing, with Knee-Action front suspension and heavy coil springs at rear. 4-Way Stabilization through dual stabilizing arms, front and rear stabilizers and lateral stabilizers at rear. Double-action hydraulic shock absorbers, front and rear.

STEERING-Dual Center-Control. Recirculating ball and nut.

Tires—Low-pressure tires, 7.60 x 15 inches. (Convertible, 8.20 x 15.)

BRAKES—Super-Hydraulic, self-energizing type. Cast iron braking surfaces. Mechanical parking brake on rear wheels. All brakes completely sealed. Brake lining area, 191.7 square inches. Front lining, 11" x 2½"; rear, 11" x 2".

WHEELBASE-122 inches, TURNING CIRCLE DIAMETER-42 feet.

Unisteel Turret-Top Bodies by Fisher, completely bonderized and finished with several coats of high grade lacquer.

Body Types—Convertible Coupe, Holiday Coupe, Club Sedan, 4-Door Town Sedan, 4-Door Sedan. (Closed models, standard and de luxe equipment available, as ordered.)